| LAARS X | SIG | | 4-20mA | |
|------------|--|---|--|--|
| | | | Interface | |
| | | | Module | |
| | | Date: | CA004200 Submittal Data Heating Systems Company | |
| | | Project #: | | |
| | | Engineer: | Project Name: | |
| | | Prepared By: | Location: | |
| | | | | |
| | | Bid Date: | Contractor: | |
| | | | | |
| Features | XSIG interface module allows an external 4-20mA setpoint sig- nal to be interfaced with Laars S8 and M4 controls | Easily connects to Laars S8, M S8EXT and M4EXT controls an expansion modules with RS48 cable (included with the XSIG) | nd 5 | |
| Dimensions | | | | |
| | 3.25" Heating Syst | Gnd 3 EXTENSION CONNECTORS | | |

Laars Heating Systems Company reserves the right to change specifications, components, features, or to discontinue products without notice.



800.900.9276 • Fax 800.559.1583 (*Customer Service and Product Support*) 20 Industrial Way, Rochester, NH 03867 • 603.335.6300 • Fax 603.335.3355 1869 Sismet Road, Mississauga, Ontario, Canada L4W 1W8 • 905.238.0100 • Fax 905.366.0130 *www.Laars.com* Litho in U.S.A. © Laars Heating Systems 1402 Document 7017A