



PRESS RELEASE

Summer 2012

High Efficiency NeoTherm LC Boiler Added to Laars Line

The new NeoTherm[®] LC condensing boiler from Laars Heating Systems is a fully packaged, 1 million or 1.7 million BTU, space-saving hydronic solution that offers 94% thermal efficiency. NeoTherm LC is a direct vent, sealed combustion boiler or volume water heater that modulates with a 10 to 1 turndown. Zero clearance to combustibles with all piping and wiring from the back make it a good choice for tight installations. The natural gas or LP-fired boiler features an ASME stainless steel heat exchanger, diagnostic information and low 10-ppm NOx emissions. Features include a large color touch screen display, pull out electrical panel, indoor or outdoor installation and a variable speed pump control option.

The NeoTherm LC includes Laars' Integrated Control System with PID logic that governs ignition, outlet water temperature, indirect water heater functions, outdoor reset, stages up to 4 boilers with the standard control, and easily integrates with other controls for multiple boiler sequencing and building automation systems.

The NeoTherm lineup also includes commercial boiler or volume water heater sizes of 285, 399, 500, 600, 750 & 850 MBH, and residential boiler sizes of 80, 105, 150, & 210 MBH.

For more information, or a list of suppliers, visit www.Laars.com.

#