MAGNATHERM® HTD BOILER OR VOLUME WATER HEATER



The Laars MagnaTherm HTD Advantage



TRU TRAC O₂ TRIM

Real time, electric fuel-to-air ratio control of combustion process results in optimized efficiency across entire 20:1 turndown



LAARS LINCTM CONTROLS

Intuitive to use, touch screen control system includes advanced features such as auto cascade, intelligent redundancy, and quick start setup



UP TO 96% THERMAL EFFICIENCY

Field proven, stainless steel heat exchanger outputs ultra-high thermal efficiencies



VARI-PRIME® PUMP CONTROL

Matches boiler modulation with variable speed boiler pump to increase total installed efficiency



FLEXIBLE INSTALLATION

A small footprint, slim vertical design and removable top section help it to fit into tight mechanical rooms

Many electrical packages available to meet job site voltage requirements; 120, 240, 480 or 600 VAC

Boiler and Volume Water Heater Models









COMMERCIAL HIGH EFFICIENCY

MAGNATHERM® HTD BOILER OR VOLUME WATER HEATER



Standing Apart from the Others

Every commercial heating system is unique and as such requires a boiler that can respond to system fluctuations, while maintaining the energy conservation standards required by today's building owners. Such a boiler exists in the innovative MagnaTherm HTD.

On board every MagnaTherm HTD boiler is the unique Tru Trac O₂ trimming system and Laars Vari-Prime pump control that balances 20:1 turndown, combustion, and water flow to dramatically reduce boiler energy consumption. MagnaTherm HTD is designed, engineered and manufactured at Laars Heating Systems, an American company.



DIMENSIONAL DATA

Dimensions [inches (cm)]			
А	В	С	D
29.3 (75)	79.8 (203)	38 (96)	57.5 (147)
29.3 (75)	79.8 (203)	38 (96)	57.5 (147)
30.8 (78)	87 (221)	41.5 (105)	60.5 (154)
30.8 (78)	87 (221)	41.5 (105)	60.5 (154)
34.5 (88)	97.5 (248)	52 (133)	70 (178)
34.5 (88)	97.5 (248)	52 (133)	70 (178)
	29.3 (75) 29.3 (75) 30.8 (78) 30.8 (78) 34.5 (88)	A B 29.3 (75) 79.8 (203) 29.3 (75) 79.8 (203) 30.8 (78) 87 (221) 30.8 (78) 87 (221) 34.5 (88) 97.5 (248)	A B C 29.3 (75) 79.8 (203) 38 (96) 29.3 (75) 79.8 (203) 38 (96) 29.3 (75) 79.8 (203) 38 (96) 30.8 (78) 87 (221) 41.5 (105) 30.8 (78) 87 (221) 41.5 (105) 34.5 (88) 97.5 (248) 52 (133)









Customer Service and Product Support: 800.900.9276 • Fax 800.559.1583 Headquarters: 20 Industrial Way, Rochester, NH 03867 • 603.335.6300 • Fax 603.335.3355 9 Brigden Gate, Halton Hills, Ontario, Canada, L7G 0A3 • 905.203.0600 • Fax 905.636.0666 www.LAARS.com