


MASCOT[®] LX



Wall Mounted, Residential Boiler

MLXH Hydronic Boiler

Indoor, Sizes 50, 75, 100, 125, 150, 175, 220

Date:

Project #:

Engineer:

Prepared By:

Bid Date:

Submittal Data



Project Name:

Location:

Contractor:

Standard Equipment

- High condensing efficiency
- Modulation down to 20% of full fire (5:1 turndown)
- Sealed combustion chamber
- Pre-mix stainless steel burner
- Low NOx system exceeds the most stringent regulations for air quality – 10ppm NOx
- Horizontal or vertical direct vent
- Vent and air pipe lengths of up to 150 equivalent feet (each)
- Horizontal vent and air terminals
- Stainless steel heat exchanger with welded construction
- ASME 30 psi (207kPa) working pressure heat exchanger
- ASME "H" stamp
- 30 psi (207kPa) ASME pressure relief valve
- Auto cascade setup
- Boiler pump wired and mounted inside jacket
- Built-in condensate trap and drain, priming not required
- Automatic air vent
- Temperature and pressure gauge
- Boiler water pressure switch
- Blocked vent pressure switch
- Blocked condensate pressure switch
- Burner site glass
- Electronic PID modulating control
- Direct spark ignition
- Multiple pump control for boiler pump and system pump, each with delay
- Domestic Hot Water Pump Output
- Customizable Freeze Protection
- Anti-short cycling
- Large user-interface and display
- Alarm output
- Accepts external (4-20mA or 0-10VDC) modulation signal
- Outdoor reset (sensor included)
- Outdoor air reset curve
- Vent temp auto turn-down before lockout
- Manual reset high limit
- Lighted on/off toggle switch
- Wall mount bracket
- Field convertible between natural gas and propane
- Zero clearance to combustible surfaces
- 15-Year limited warranty
- 2-Year parts warranty

Boiler Data

Number of Units:

Fuel

- ☐ Natural
☐ Propane

Options

- ☐ Low Water Cut-off



Accessories for Field Mounting

☐ Horizontal concentric vent kit	☐ Concentric elbow, 90°	☐ Concentric flush-mount 2" terminal
☐ Concentric vent adapter	☐ Wall plate for concentric pipe	☐ Concentric flush-mount 3" terminal
☐ Concentric pipe, 12" long	☐ Horizontal concentric sssl terminal	☐ Condensate Neutralizer
☐ Concentric pipe, 24" long	☐ Horizontal concentric 2" PVC terminal	
☐ Concentric pipe, 36" long	☐ Horizontal concentric 3" PVC terminal	
☐ Concentric pipe, 13"-18" telescoping		

Sizing Data

Model	Input		Output		Gas Conn. Size inches	Water Conn. Size inches	Boiler Shipping Weight	
	BTU/h	kW	BTU/h	kW			lbs	kg
☐ MLX H 50	50,000	14.6	47,500	13.2	1/2" NPT	3/4" NPT	88	40
☐ MLX H 75	75,000	21.9	71,250	20.8	1/2" NPT	3/4" NPT	97	44
☐ MLX H 100	100,000	29.3	95,000	27.8	1/2" NPT	3/4" NPT	112	51
☐ MLX H 125	125,000	36.6	118,750	34.8	1/2" NPT	3/4" NPT	126	57
☐ MLX H 150	150,000	43.9	142,500	41.8	1/2" NPT	1" NPT	140	64
☐ MLX H 175	175,000	51.6	166,250	48.7	1/2" NPT	1" NPT	153	69
☐ MLX H 220	220,000	64.4	209,000	61.2	1/2" NPT	1" NPT	161	73

NOTES:

1. For other boiler ratings:

$$\text{Boiler Horsepower: HP} = \frac{\text{Output}}{33,475} \quad \text{Radiation Surface: EDR sq. ft.} = \frac{\text{Output}}{150}$$

Electrical Data

Size	Boiler		
	Volts	Phase	Amps
MLXH 50	120	Single	1.5
MLXH 75	120	Single	1.5
MLX H 100	120	Single	1.5
MLX H 125	120	Single	1.5
MLX H 150	120	Single	1.5
MLX H 175	120	Single	2.2
MLX H 220	120	Single	2.2

* Minimum 15A circuit required

Vent System

INTAKE / EXHAUST Max Equivalent Vent and Air Pipe Length (each)									
SIZES	STANDARD 2-PIPE			STANDARD 2-PIPE			OPTIONAL CONCENTRIC		
	DIA.	FT.	m	DIA.	FT.	m	DIA.	FT.	m
50 - 175	2"	40	12.2	3"*	150	45.7	3/5"	40	12.2
220	2"	30	9.1	3"*	120	36.6	3/5"	40	12.2


* Must use 2x3 adapter within 1 ft. (30cm) of boiler.

Reference the Installation and Operation Manual for more details.

**Dimensional
Data**



Model	Dimension							
	A	B	C	D	E	F	G	H
50, 75 MBH	1" (3)	15-3/4" (40)	3-3/4" (9)	9-1/4" (24)	8" (20)	1-1/2" (4)	5-3/4" (14)	15-1/2" (39)
100, 125 MBH	1" (3)	15-1/2" (39)	1-1/4" (3)	12-3/4" (33)	11" (28)	1-1/4" (3)	9-1/2" (24)	14-3/4" (37)
150, 175 MBH	1-1/2" (4)	15-1/4" (39)	1-3/4" (4)	13" (33)	11-1/4" (28)	2-3/4" (7)	5-1/4" (14)	2" (5)
220 MBH	1-1/2" (4)	15-1/4" (39)	1-3/4" (4)	13" (33)	11-1/4" (28)	2-3/4" (7)	5-1/4" (14)	2" (5)

inches (cm)




Model	M	N	O
50, 75 MBH	30-1/2" (78)	15-1/4" (39)	4-5/8" (12)
100, 125 MBH	30-1/2" (78)	18" (46)	4-5/8" (12)
150, 175 MBH	35-1/2" (90)	18" (46)	8-7/8" (23)
220 MBH	38-1/2" (90)	18" (46)	8-7/8" (23)

inches (cm)



Clearances

APPLIANCE SURFACE	SUGGESTED SERVICE ACCESS CLEARANCE	
	INCHES	CM
Left Side	6	15
Right Side	6	15
Top	12	30
Closet, Front	6	15
Front	24	61
Bottom	24	61
Vent	1	3
Certified by CSA for zero clearance to combustible materials on all sides.		



Laars Heating Systems Company reserves the right to change specifications, components, features, or to discontinue products without notice.



Customer Service and Product Support: 800.900.9276 • Fax 800.559.1583
Headquarters: 20 Industrial Way, Rochester, NH, USA 03867 • 603.335.6300 • Fax 603.335.3355
9 Brigden Gate, Halton Hills, Ontario, Canada L7G 0A3 • 905.203.0600 • Fax: 905.636.0666
www.Laars.com

Litho in U.S.A. © Laars Heating Systems 20-02 Document 1299E